



TECHNICAL DATA

Composición / Composition Composition / Composizione	70% PVC + 25% Fiberglass
Ancho de rollo / Largeur rouleau Roll width / Larghezza del tessuto	300 cm / 118 "
Grado de apertura / Coefficient d'ouverture Openess Factor / Grado di apertura	Aprox. 0%
Espesor / Épaisseur Thickness / Spessore	0,40 mm ± 5% / 0,016 " ± 5%
Peso / Poids Weight / Peso	570 gr/m² ± 5% / -
Resistencia al fuego / Classement feu Fire classification / Resistenza al fuoco	NFPA 701 : Pass
Certificación Ambiental / Certification Environnementale Environmental Certification / Certificazione ambientale	-
Absorción acústica / Absorption acoustique Sound absorption / Assorbimento acustico - (ISO 10534:2)	-
Resistencia a la luz / Resistance a la lumiere Light Fastness / Resistenza alla luce - (Grey Scale / Blue Scale)	- / >4,5 Xenotest Grade
Resistencia al desgarro / Résistance à la déchirure Tear resistance / Resistenza alla rottura - (EN ISO 13937-3)	164 N/5 cm - 157 N/5 cm
Resistencia a la ruptura / Résistance à la rupture Tensile strength / Resistenza alla rottura - (EN ISO 13934-1)	-

OTHER CERTIFICATIONS



WASHING INSTRUCTIONS




FABRIC COLOURS



WHITE
Ref. 40003L



LIGHT GREY
Ref. 40004L



BLACK
Ref. 40006L



ALABASTER
Ref. 40007L



CUSTARD
Ref. 40001L



STONE
Ref. 40016L